Certificate Number: 01-HS109481D/3-PDA



## Confirmation of Product Type Approval 21/MAR/2011

Please refer to the "Service Restrictions" shown below to determine if Unit Certification is required for this product.

This is to certify that, pursuant to the Rules of the American Bureau of Shipping (ABS), the manufacturer of the below listed product held a valid Manufacturing Assessment (MA) with expiration date of 20/NOV/2013. The continued validity of the Manufacturing Assessment is dependent on completion of satisfactory audits as required by the ABS Rules.

And; a Product Design Assessment (PDA) valid until 10/JAN/2015 subject to continued compliance with the Rules or standards used in the evaluation of the product.

The above entitle the product to be called Product Type Approved.

The Product Design Assessment is valid for products intended for use on ABS classed vessels, MODUs or facilities which are in existence or under contract for construction on the date of the ABS Rules used to evaluate the Product.

ABS makes no representations regarding Type Approval of the Product for use on vessels, MODUs or facilities built after the date of the ABS Rules used for this evaluation.

Due to wide variety of specifications used in the products ABS has evaluated for Type Approval, it is part of our contract that; whether the standard is an ABS Rule or a non-ABS Rule, the Client has full responsibility for continued compliance with the standard.

## TIDES MARINE INC. Model Name(s): RPB- C, D, E, G, H, TS

To provide a Sealed Rudder Bearing for New Construction or Retrofits of Pleasure and Commercial Vessels.	
A Rudder Bearing System providing a Bearing Surface with integral Seal. Available in a GRP Tube for GRP Constructed Vessels.	
For Rudder Stock Sizes : 1" - 8" or 25 mm - 200 mm.	
Unit Certification is not required for this product.	
1.) The lip seal is to be suitable for the intended service. 2.) The equipment should be visually inspected by the attending Surveyor during periodic surveys, with particular attention being given to the nitrile lip seals. These are to be replaced if deemed necessary. 3.) The manufacturer's recommended installation procedures are to be followed.	
This Product Design Assessment (PDA) is valid only for products intended for use on ABS classed vessels, MODUs or facilities which are in existence or under contract for construction on the date of the ABS Rules used to evaluate the Product.	
This product/model is covered under Product Design Assessment (PDA) Certificate # 01-HS109481D/3-PDA, dated 11/Jan/2010. This PDA Certificate expires 10/Jan/2015. It will remain valid for 5 years from date of issue or until the Rules or specifications used in the assessment are revised (whichever occurs first). It is valid for all vessels contracted on or before the date of the Rules used in this evaluation.	

ABS Rules:	2010 Steel Vessels Rules 1-1-4/7.7; 2000 Guide for Building and Classing Motor Pleasure Yachts Section 13; 2001 Guide for Building and Classing High-Speed Craft 3/5.13		
National Standards:	2005 ABYC Recommendations,		
International Standards: Government Authority: EUMED:			
Others:	Refer to the Manufacturer's Website (www.tidesmarine.com) for Standards, Ratings and Sizes		
Model Certificate	Model Certificate No	Issue Date	Expiry Date
PDA	01-HS109481D/3-PDA	11/JAN/2010	10/JAN/2015
		(*	ABS Programs
date and time the certificate was print manufacturer's quality assurance and Approval. The approvals of Drawings cautions manufacturers to review and unless it is specifically indicated in the procedures (where otherwise required	reparation of this certificate and it repres ted. Type Approval requires Drawing As d quality control arrangements. Limited c and Products remain valid as long as th d maintain compliance with all other spee e description of the product; Type Appro d) for products to be used in a vessel, M the validity of ABS Rules or the need for	sessment, Prototype Testing circumstances may allow only ne ABS Rule, to which they v cifications to which the produ- oval does not necessarily wai IODU or facility intended to b	product in the ABS Records as of the g and assessment of the y Prototype Testing to satisfy Type were assessed, remains valid. ABS uct may have been assessed. Further, ive witnessed inspection or survey be ABS classed or that is presently in