Impeller Pump OP-6

Impeller pump suitable for quick transfer of diesel, oil or water. Flow is in direction of reversible switch with safety lock.


Basic Features

- · Reversible: Transfers diesel, oil, or water
- 3-Position switch (ON-OFF-ON)
- Safety lock prevents accidental activation

A CONTRACTOR OF THE PARTY OF TH

Technical Specifications

Flow Rate	3 GPM / 11.35 LPM		
Voltage	12V or 24V		
Port	Exterior		3/4" Male Hose
	Interior		3/8" Female NPT
Amp. Draw	3.4A / 12V, 3A / 24V		
Pump Type	Impeller		
Self-Priming	3 ft / 0.9m (wet gears)		
Fuse	15A / 12V, 10A / 24V		
Dimensions	Α	9.5" / 240 mm	
	В	4" / 101 mm	
	С	3.5" / 89 mm	



Spare Parts

Impeller	Nitrile for oil / water	38-2313		
	Fluoroelastomer for diesel	38-2314		
Fuse	15A for 12V	03-0639		
	10A for 24V	03-0637		
Repair Kit: Impeller & Gasket	1 Oil / Water Set	38-0360		
	2 Oil / Water Sets	38-0360-02		
	1 Diesel / Oil / Water Set	38-0370		
	2 Diesel / Oil / Water Sets	38-0370-02		
Rebuild Kit: Impeller, Gasket, & Seals	1 Oil / Water Set	38-0361		
	2 Oil / Water Sets	38-0361-02		
	1 Diesel / Oil / Water Set	38-0371		
	2 Diesel / Oil / Water Sets	38-0371-02		

Safety Lock

The pump has a safety lock that covering the switch to safeguard against accidental activation. Lift safety lock to get to switch.



Flow Direction

The direction the switch is flipped determines the direction of flow.



Version: 6/10/11

